

MANUFACTURE STANDARD, MANUFACTURE RELIANCE

RAC 050

Auto Coagulation Analyzer

NEW



Features

- Random Access, smart and compact
- Clotting, Chromogenic, Immunologic measuring methods
- User friendly touchscreen interface, simple & easy to operate
- High throughput routine assays
- Labor saving, simple programming and real walk-away system
- Reagent open system, close system on request
- Multi-language software(optional)

RAC 050

Auto Coagulation Analyzer



Technical Specifications

System Function

- Throughput: 60 tests/hour for PT
50 tests/hour for PT and APTT
- Parameters: PT, APTT, TT, FIB, AT-III, PLG, D-Dimer, FDP, etc.
- Measuring methods:
Clotting: Scattered Light Detection method
Chromogenic: Colorimetric method, 405nm
Immunologic: Turbidimetric method, 575nm
- Memory: 100,000 test results and 10,000 reaction curves
- Quality control: 12 QC File*10 test items*30 curve*12 month
- Calibration: 6 points*10 items
- Automatic, Random Access
- STAT sample priority
- Auto re-diluent/ re-test
- Barcode-reading support (optional)

Sample Tray

- Sample tray: 27 positions, user-defined STAT
- Incubation temperature: $37 \pm 0.5^\circ\text{C}$

Reagent Tray

- Reagent tray: 23 positions
- Reagent cooling: $\leq 16^\circ\text{C}$

Reaction Tray

- Cuvettes on board : 72
- Min reaction volume: 150ul
- Reaction temperature: $37 \pm 0.5^\circ\text{C}$

Probe

- With probe pre-heating
- Automatic washing both inside and outside
- With collision protection, liquid level detection and Inventory checking

Print out

- Built-in thermal printer, external printer optional

Measuring and Optic System

- Light: LED
- Power: AC 110/240V, 50-60 \pm 1Hz
- Temperature: 10°C - 30°C , humidity \leq 85%
- Water consumption: <0.5L/hour
- Dimension L \times W \times H (mm) : 660 \times 580 \times 510
- Weight: 53KG



7 Detection Channels

- 5 for clotting assays
- 1 for chromogenic assays
- 1 for immunologic assays



Sample/Reagent Probe with Liquid Level Detection

Status Menu



Rayto Life and Analytical Sciences Co.,Ltd.

2nd Floor, 5th Building, Software Park, NO.2, Gaoxinzhong
3rd Road, High-tech Industrial Park, Nanshan,
Shenzhen 518057, P.R.China
Tel:+86(755)86168996 Fax:+86(755)86168796
Email:info@rayto.com

